



- Internal size 510mm x 510mm x 330mm.
- 4.5kw single phase.
- 960c maximum temperature.
- Quartz tube "infra-red" heating system.
- Stainless Steel chamber and base.
- Lid spring lift assist.
- 110mm recess in floor.
- KCR32C digital Control with 32 programs and 32 ramps.
- Optional KCR32CWIFI control with GATEway internet access.
- Kilncare unique KCX over temperature, in built protection.
- Fast react thermocouple.
- Non ceramic fibre lid section.
- Light weight refractory brick base.
- Large vent/spy hole with spring return, anti-dust flap.
- Optional stand and inner shelf kit.
- Optional lockable swivel castors for stand.
- Designed and built by Kilncare in the U.K.
- **FOUR years guarantee on ALL parts INCLUDING the elements.**

**The Cub-fuser-D and the Cub-fuser are the 2nd members to the "fuser" family of glass kilns.**

The Cub-fuser-D fills in the gap between Hobbyfuser 3 and Pro-fuser-D.

Essentially the "Cub" is identical in every respect to the larger "Pro" except for width.

As with the Pro-D, the Cub-D is controlled via the KCR32C programmer.

The **KCR32CWIFI** is an optional extra which allows your kiln to be monitored over the internet using the Kilncare GATEway server.

There are many features inside the GATEway such as a program and firing library and writing programs inside the GATEway, naming them and then sending them to the controller.

The Cub-D features the unique **KCX electronic over temperature system**. The KCX is integral to the inner wiring of the kiln and will shut the kiln down and provide audible warning in the event of a kiln over temperature fault.

The KCX works independently of any safety systems in the KCR32C and makes the Cub-fuser-D unique in having in built over-fire safety.

# **KILN***care*

The Kiln Works, 907 Leek New Road, Baddeley Green, Stoke on Trent, Staffs, United Kingdom, ST2 7HQ  
TEL/FAX 0044 1782 535915, 535338 e-mail [sales@kilncare.co.uk](mailto:sales@kilncare.co.uk) Web [www.kilncare.co.uk](http://www.kilncare.co.uk)